

CLAIMS

1. A speech correction method for correcting misrecognized text in a speech recognition application comprising the steps of:
- receiving audio speech input and speech-to-text converting said received audio speech input to speech recognized text;
 - detecting in said speech recognized text a first speech correction command for performing a correction operation on speech recognized text stored in a text buffer;
 - if a first speech correction command is not detected in said speech recognized text, adding said speech recognized text to said text buffer; and,
 - if a first speech correction command is detected in said speech recognized text, performing said detected speech correction command on speech recognized text stored in said text buffer.
2. The method according to claim 1, wherein said receiving step further comprises the step of:
- audibly confirming said speech-to-text conversion of said speech recognized text.
3. The method according to claim 2, wherein said step of audibly confirming said speech-to-text conversion of said speech recognized text comprises the step of:

4 audibly playing back said speech recognized text so that it can be determined if
5 said recorded speech recognized text had been misrecognized in said speech-to-text
6 converting step.

1 4. The method according to claim 1, further comprising the step of:
2 responsive to detecting said first speech correction command in said speech
3 recognized text, said first speech correction command indicating a preference to
4 terminate said speech correction method, determining if said speech recognized text
5 stored in said text buffer had been spelled out;
6 adding said speech recognized text determined to have been spelled out to a
7 speech recognition vocabulary of speech recognizable words; and,
8 terminating said speech correction method.

9 5. The method according to claim 1, further comprising the step of:
10 responsive to detecting said first speech correction command in said speech
11 recognized text, said first speech correction command indicating a preference to correct
12 misrecognized text in said text buffer, audibly playing a list of speech correction
13 candidates, wherein each speech correction candidate in said list is statistically
14 alternative recognized text to said audio speech input;
15 receiving a selection of one of said speech correction candidates in said list; and,

8 replacing said misrecognized text in said text buffer with said selected speech
9 correction candidate.

1 6. The method according to claim 1, further comprising the steps of:
2 responsive to detecting said first speech correction command in said speech
3 recognized text, said first speech correction command indicating a preference to correct
4 misrecognized text in said text buffer, audibly playing a list of speech correction
5 candidates, wherein each speech correction candidate in said list is statistically
6 alternative recognized text to said audio speech input;

receiving a second speech correction command, said second speech correction
command indicating both preferred replacement text and a preference to replace said
misrecognized text with said preferred replacement text in said text buffer; and,

responsive to receiving said second speech correction command, replacing said
misrecognized text in said text buffer with said preferred replacement text.

1 7. The method according to claim 1, further comprising the steps of:
2 responsive to detecting said first speech correction command in said speech
3 recognized text, said first speech correction command indicating a preference to correct
4 misrecognized text in said text buffer, audibly playing a list of speech correction
5 candidates, wherein each speech correction candidate in said list is statistically
6 alternative recognized text to said audio speech input;

7 receiving a second speech correction command, said second speech correction
8 command indicating a preference to replace said misrecognized text in said text buffer
9 with spelled-out replacement text;

10 responsive to receiving said second speech correction command, accepting
11 audibly spelled-out replacement text, said audibly spelled-out replacement text
12 comprising a series of spoken alphanumeric characters;

13 speech-to-text converting said series of spoken alphanumeric characters, each
14 speech-to-text converted alphanumeric character stored in a temporary buffer, and
15 combining said speech-to-text converted alphanumeric characters into spelled out
16 replacement text; and,

17 replacing said misrecognized text in said text buffer with said spelled out
18 replacement text.

8. The method according to claim 7, further comprising the steps of:

1 detecting in said audibly spelled-out replacement text, a third speech correction
2 command, said third speech correction command indicating a preference to delete a
3 particular alphanumeric character stored in said temporary buffer; and,
4

5 responsive to detecting said third speech correction command, deleting said
6 particular alphanumeric character from said temporary buffer.

1 9. The method according to claim 7, further comprising the steps of:

2 detecting in said audibly spelled-out replacement text, a third speech correction
3 command, said third speech correction command indicating both a preferred
4 replacement alphanumeric character and a preference to replace a particular
5 alphanumeric character with said preferred replacement alphanumeric character in said
6 temporary buffer; and,

7 responsive to detecting said third speech correction command, replacing said
8 particular alphanumeric character with said preferred alphanumeric character in said
9 temporary buffer.

10. The method according to claim 7, wherein said accepting step further comprises
the step of:

prior to accepting audibly spelled out replacement text, playing a pre-stored set
of instructions for providing said spelled out replacement text.

11. A machine readable storage, having stored thereon a computer program having
a plurality of code sections for performing a speech correction method for correcting
misrecognized text in a speech recognition application, said code sections executable
by a machine for causing a machine to perform the steps of:

receiving audio speech input and speech-to-text converting said received audio
speech input to speech recognized text;

7 detecting in said speech recognized text a first speech correction command for
8 performing a correction operation on speech recognized text stored in a text buffer;
9 if a first speech correction command is not detected in said speech recognized
10 text, adding said speech recognized text to said text buffer; and,
11 if a first speech correction command is detected in said speech recognized text,
12 performing said detected speech correction command on speech recognized text
13 stored in said text buffer.

12. The machine readable storage according to claim 11, wherein said receiving
step further comprises the step of:

audibly confirming said speech-to-text conversion of said speech recognized
text.

13. The machine readable storage according to claim 12, wherein said step of
audibly confirming said speech-to-text conversion of said speech recognized text
comprises the step of:

audibly playing back said speech recognized text so that it can be determined if
said recorded speech recognized text had been misrecognized in said speech-to-text
converting step.

1 14. The machine readable storage according to claim 11, further comprising the step
2 of:

3 responsive to detecting said first speech correction command in said speech
4 recognized text, said first speech correction command indicating a preference to
5 terminate said speech correction method, determining if said speech recognized text
6 stored in said text buffer had been spelled out;

7 adding said speech recognized text determined to have been spelled out to a
8 speech recognition vocabulary of speech recognizable words; and,

9 terminating said speech correction method.

10 15. The machine readable storage according to claim 11, further comprising the step
of:

responsive to detecting said first speech correction command in said speech
recognized text, said first speech correction command indicating a preference to correct
misrecognized text in said text buffer, audibly playing a list of speech correction
candidates, wherein each speech correction candidate in said list is statistically
alternative recognized text to said audio speech input;

receiving a selection of one of said speech correction candidates in said list; and,
replacing said misrecognized text in said text buffer with said selected speech
correction candidate.

1 16. The machine readable storage according to claim 11, further comprising the
2 steps of:

3 responsive to detecting said first speech correction command in said speech
4 recognized text, said first speech correction command indicating a preference to correct
5 misrecognized text in said text buffer, audibly playing a list of speech correction
6 candidates, wherein each speech correction candidate in said list is statistically
7 alternative recognized text to said audio speech input;

8 receiving a second speech correction command, said second speech correction
9 command indicating both preferred replacement text and a preference to replace said
10 misrecognized text with said preferred replacement text in said text buffer; and,

11 responsive to receiving said second speech correction command, replacing said
12 misrecognized text in said text buffer with said preferred replacement text.

13 17. The machine readable storage according to claim 11, further comprising the
14 steps of:

15 3 responsive to detecting said first speech correction command in said speech
16 4 recognized text, said first speech correction command indicating a preference to correct
17 5 misrecognized text in said text buffer, audibly playing a list of speech correction
18 6 candidates, wherein each speech correction candidate in said list is statistically
19 7 alternative recognized text to said audio speech input;

8 receiving a second speech correction command, said second speech correction
9 command indicating a preference to replace said misrecognized text in said text buffer
10 with spelled-out replacement text;

11 responsive to receiving said second speech correction command, accepting
12 audibly spelled-out replacement text, said audibly spelled-out replacement text
13 comprising a series of spoken alphanumeric characters;

14 speech-to-text converting said series of spoken alphanumeric characters, each
15 speech-to-text converted alphanumeric character stored in a temporary buffer, and
16 combining said speech-to-text converted alphanumeric characters into spelled out
17 replacement text; and,

18 replacing said misrecognized text in said text buffer with said spelled out
19 replacement text.

20 18. The machine readable storage according to claim 17, further comprising the
21 steps of:

22 3 detecting in said audibly spelled-out replacement text, a third speech correction
23 4 command, said third speech correction command indicating a preference to delete a
24 5 particular alphanumeric character stored in said temporary buffer; and,

25 6 responsive to detecting said third speech correction command, deleting said
26 7 particular alphanumeric character from said temporary buffer.

1 19. The machine readable storage according to claim 17, further comprising the
2 steps of:

3 detecting in said audibly spelled-out replacement text, a third speech correction
4 command, said third speech correction command indicating both a preferred
5 replacement alphanumeric character and a preference to replace a particular
6 alphanumeric character with said preferred replacement alphanumeric character in said
7 temporary buffer; and,

8 responsive to detecting said third speech correction command, replacing said
9 particular alphanumeric character with said preferred alphanumeric character in said
10 temporary buffer.

11 20. The machine readable storage according to claim 17, wherein said accepting
12 step further comprises the step of:

13 prior to accepting audibly spelled out replacement text, playing a pre-stored set
14 of instructions for providing said spelled out replacement text.